



TECHNICAL DATA SHEET
REVISION: 0
DATE: 20/01/2022



KLEBENRAD PU 70

3D PRINTING RESIN

CHARACTERISTICS

DESCRIPTION

KLEBENRAD PU 70 is a high-quality rigid polyurethane resin for 3D printing. Sensitive to 405nm UV wavelength.

Compatible with most DLP/LCD 3D printers.

PHYSICAL PROPERTIES

Norm

Shore D hardness **70**

MAIN FEATURES

- **Rigid finish**
- **High tenacity**
- **Low yellowing**
- **High print speed**
- **High chemical resistance post curing**
- **Color range**
- **High finishing precision**
- **Sharp and defined edges**
- **Mind odor**
- **Solvent free**
- **Low toxicity**
- **Easy to clean with Isopropanol**

PRINTING PARAMETERS

- Layer thickness recommended between 50 – 100 microns per layer.
- Exposure time recommended between 5 – 10 seconds, depending on the thickness of the layer.
- The first 6 layers are recommended with a minimum thickness of 50 microns and an exposure time of 30 seconds per layer to secure the model to the printing platform. For large pieces, increase the number of layers.
- Minimum distance of rise/fall of the axis between layers: 10 mm.
- Minimum delay time before exposure: 2 seconds.

POST CURING PARAMETERS

- Between 15 and 30 minutes, with a 200 W 405 nm UV LED light, depending on the thickness and color of the piece.

RECOMMENDATIONS

- Shake well before use to homogenize the content.
- Recommended temperature: 20 – 25 °C. At lower temperatures the viscosity of the resin will increase and make the printing process more difficult.
- Always wear gloves, in case of staining the skin, wash it with plenty of warm water and soap.
- Use it in well-ventilated areas.
- Store protected from direct sunlight and keep it out of the children`s reach.
- If the resin inside the printing tank is not going to be used for a long period of time, it is recommended to pour it into the original container using a fine filter to prevent remains of polymerized resin or contamination. After, close the container and store it in a clean and dry place.
- Keep the machine's protective cover protecting the print reservoir, even when printing is not working.

SUPPLY/ STORAGE

In recyclable plastic containers of 0.5, 1 and 5 kg.

It can be stored for 1 year in its original closed container.

KLEBENTECH S.L.
Camí Pascualeta, 6
46200 Paiporta, Valencia - España
+34 961 849 409
info@klebentech.com / www.klebentech.com



KLEBENRAD is a product developed and manufactured by Klebentech S.L. The KLEBENRAD trademark is registered. Its use, modification, dissemination, or reproduction of any printed or digital content associated with the brand without the express authorization of the company is prohibited.